



Ref. **4600****FRESA FRONTAL ACABADO HSSE 8% CO NZ**

NZ HSSE 8% Co Finishing End Mill

Fraise finition HSSE 8% Co NZ



Material		Vc (m/min)		Avances fz/rev. (mm/z) - Feed - Pas									
Grupo	Sub.	8% Co	TIALSIN	Ø 4	Ø 6	Ø 8	Ø 10	Ø 12	Ø 16	Ø 20	Ø 25	Ø 32	Ø 40
P	P.1	25-35	35-46	0,020	0,030	0,035	0,050	0,060	0,100	0,100	0,100	0,100	0,100
K	K.1	20-30	25-45	0,020	0,030	0,035	0,050	0,060	0,100	0,100	0,100	0,100	0,100
	K.2	15-20	20-25	0,014	0,030	0,035	0,050	0,060	0,100	0,100	0,100	0,100	0,100
N	N.1	60-100	80-140	0,020	0,030	0,035	0,050	0,060	0,100	0,100	0,100	0,100	0,100
	N.2	60-100	80-140	0,020	0,030	0,035	0,050	0,060	0,100	0,100	0,100	0,100	0,100

$$r.p.m. = \frac{Vc \times 1.000}{\pi \times \phi}$$

K = Coeficiente corrección
Correction coefficient
Coefficient correction

$$Vf (mm/min.) = r.p.m. \times Z \times fz \times K$$

D mm	d mm	L mm	l mm	Z	Nº Art. 8% Co
24,00	25	121	45	6	77694

**ESPECIFICACIONES:****DETALLES TECNICOS**

DIN ⓘ

844

Mat Hta ⓘ

HSSE 8% Co

d mm ⓘ

25.00

l mm ⓘ

45.00

Angulo Helice ⓘ

30°

Uds Pack ⓘ

1

Tipo DIN ⓘ

N

D mm ⓘ

24.00

L mm ⓘ

121

Z ⓘ

6

Mango

Weldon

ISO ⓘ

1641

